



PRODUCT DATA SHEET

5W-30 SN/CF

Four seasons engine oil which has been formulated with synthetic base oils and performance additives for superior protection and excellent fluidity. It has been developed to be used in gasoline and diesel engines passenger and commercial vehicles engines. It can be safely used in cars, vans and small commercial vehicles engines.

Properties

- Provides fuel economy and long service life by excellent viscosity control property.
- It forms extra protection layer against to abrasion by bonding to surface of engines with smart molecules that contains.
- It makes easy to work at cold weather by its viscosity.
- Provides high resistance to tear due to high viscosity index.

Approvals and Specifications

API: SN Plus, API: SN/CF, ACEA C5-16, MB:229.71, BMW: Longlife-17 FE+, CHRYSLER: MS6395, VW:508.00/509.00/TL 52 577, PORSCHE: C20, FIAT: 9.55535-CR1/9.55535-GSX, FORD WSS-M2C945-A/WSS-M2C946-A/WSS-M2C947-A, GM: dexosD/dexos1 Gen 2, OPEL: 0V0401547, VOLVO: VCC RBS0-2AE.

TEST	METHOD	TYPICAL PROPERTIES
Density, g/cm ³ , at 15°C	ASTM D4052	0,869
Kinematic Viscosity, at 40 °C	ASTM D 455	68,8
Kinematic Viscosity, cSt, at 100°C	ASTM D445	11,8
Viscosity Index	ASTM D2270	165
Flash Point, °C, min	ASTM D92	236
Pour Point, °C, max	ASTM D97	-30
Ash, Sulfated, mass%,	ASTM D874	0.6