



## PRODUCT DATA SHEET

# GEAR OIL EP 80W-90

### Description:

High quality paraffinic base oils based EP (extreme pressure), rust and corrosion prevention with the latest technology are produced by adding a special additive package.

### Performance Features and Benefits:

- Prevents metal to metal contact,
- Very good thermal resistance,
- Minimum viscosity change, optimum film capability,
- Bronze alloys corrosion protection,
- Long service life,
- Economy in the cost of lubrication,
- Additive which prevents wear and extreme pressure (EP) additive, includes a gear system maintains very good fittings.

### Application:

Cars, trucks, buses, light commercial vehicles, agricultural vehicles and machines as well as many tool in the gearbox and differential, spiral bevel, hypoid gear system used in the four seasons.

### Performance specifications:

API: GL-5 meet the performance specifications.

### Typical Characteristics:

Physical Properties	EP 80W-90
Density, g/cm <sup>3</sup> , at 15°C	0,890
Kinematic Viscosity, cSt, at 40°C min.	160
Kinematic Viscosity, cSt, at 100°C	15,2
Viscosity Index min.	95
Pour Point, °C, max	-18
Flash Point, °C, min	225

*\* The values specified in the table are typical values and may vary based on production.*

[www.cosmomotoroil.com](http://www.cosmomotoroil.com)